


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

BRADFORD POST



FB255



RoHS compliant

EXAMPLE # FB255-I60-BC-LWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FB255	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 -13W Power Input W -900lm 3000K CRI 80 (TYP) C -1000lm 4000K >65 Lumens Per Watt**	W -White B -Black	ACRYLIC C -Clear W -White F - Glare Free Frost	N/A
	INCANDESCENT, MEDIUM BASE, 120V I60 -1 X 60W Max	W -White B -Black	ACRYLIC C -Clear W -White F - Glare Free Frost	LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE -A19/E26, 2700K LCE -A19/E26, 4000K
	GU24 BASE, 120V G13 -1 X 13W G18 -1 X 18W G23 -1 X 23W G26 -1 X 26W or 27W	W -White B -Black	ACRYLIC C -Clear W -White F - Glare Free Frost	L -CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.