


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 6

FITTER NECK POCKET JELLY JAR



FP101



RoHS compliant



EXAMPLE # FP101-I60-BG-PLWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FP101	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR LE800 -13W Power Input W -900lm 3000K CRI 80 (TYP) C -1000lm 4000K >65 Lumens Per Watt**	W -White B -Black	P -POLYCARBONATE C -Clear G - GLASS G - Clear	P -Photocell
	INCANDESCENT, MEDIUM BASE, 120V I60 -1 X 60W Max	W -White B -Black	P -POLYCARBONATE C -Clear G - GLASS G - Clear	P -Photocell LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE -A19/E26, 2700K LCE -A19/E26, 4000K
	GU24 BASE, 120V G13 -1 X 13W G18 -1 X 18W G23 -1 X 23W	W -White B -Black	P -POLYCARBONATE C -Clear G - GLASS G - Clear	P -Photocell L -CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.