


OPEN CORE & COIL BALLAST SINGLE LAMP WITHOUT BRACKET


- Product Specifications listed below
- Magnetic Ballast Warranty Info in back of this section



CASE STYLES

	A	B	C
3	1 11/16"	1 21/32"	2
3A	2 1/32"	1 13/32"	1 11/16"

WIRING DIAGRAM



CUSTOM LEAD LENGTHS AVAILABLE. CALL FOR DETAILS.

Lamp Data		Part #	Circuit Electrical Data						Physical Data			Certification
Watts	Model#		Volts	Hz	Line Current (Amps)	Input (Watts)	Minimum Starting Temp	Sound Rating	Case Style	Std. Pkg	Weight	
13	CFT13W/GX23 CFQ13W/GX23	†IG120-220	120	60	0.260	15	32°F	A	3	100	66lbs.	UR-CUR
13	CFT13W/GX23 CFQ13W/GX23	*†IG120-220B	120	60	0.260	15	32°F	A	3	100	66lbs.	UR-CUR
13	CFT13W/GX23 CFQ13W/GX23	†IG130SNF	120	60	0.30	15	32°F	A	3A	50	33lbs.	UR-CUR
15,18,20	F15T8	†IG130-220	120	60	0.26	15.4	32°F	A	3	100	55lbs.	UR-CUR
	F18T8		120	60	0.23	14.5	32°F	A	3	100	55lbs.	UR-CUR
	F20T12		120	60	0.22	15.9	32°F	A	3	100	55lbs.	UR-CUR
15,18,20	F15T8	*†IG130-220B	120	60	0.26	15.4	32°F	A	3	100	55lbs.	UR-CUR
	F18T8		120	60	0.23	14.5	32°F	A	3	100	55lbs.	UR-CUR
	F20T12		120	60	0.22	15.9	32°F	A	3	100	55lbs.	UR-CUR

* Class B Insulation

† Non-stocked, Special Order, Call for details



NOTE: All Ballasts Type 1, Outdoor